



GM Monograde Engine Oil

SAE 30 & 50

Previously known as RoadMaster 200

Description

GardenMaster (GM) Monograde (Mono) SAE 30 & 50 meet API SL/CF and JASO performance specifications.

Applications

GM Mono SAE 30 & 50 is ideal for 4 stroke lawnmower engines, pumps, generators and older vehicles calling for monograde oils of these viscosity grades. It is mainly used in garden machinery with petrol engines where manufacturers recommend API SJ/SL or earlier specifications. It is also suitable for diesel units requiring API CD or CF lubricants.

Features & Benefits

GM Mono SAE 30 & 50 is blended from high quality base oils fortified with a balanced additive package to provide:

- High level of engine protection against engine sludge, varnish deposits and wear
- Reduction in wear in the valve train mechanism
- Increased resistance to oil oxidation
- Excellent carbon deposit control for performance retention over time
- Low temperature fluidity for easy start in cold conditions
- Reduced volatility for low oil consumption

Specifications

Properties	Method	SAE 30	SAE 50
Specific Gravity @ 20°C	ASTM D1298	0.873	0.886
Kinematic Viscosity @ 40°C	ASTM D445	90.8	201.8
Kinematic Viscosity @ 100°C	ASTM D445	10.62	18.01
Viscosity Index	ASTM D2270	99.5	97.5
Phosphorus %Wt	ASTM D3231	0.11	0.11

Performance Levels

API SL/SJ	API CF	JASO T903:2011
-----------	--------	----------------

Master Item# 1109 & 1111

Pack Size Availability: SAE 30; 1L, 5L, 20L, 200L, IBC=1000L
SAE 50; 20L, 200L, IBC=1000L

Last Updated: 15th December 2023
Previously Updated: 28th September 2021