



# RM Auto Premium MV

## Low Viscosity

Previously known as Auto Type MV Low Vis

### Description

RoadMaster (RM) Auto Premium MV Low Viscosity is a premium quality full synthetic transmission fluid blended to suit the frictional requirements of a wide range of transmissions of most of the major manufacturers requiring Low Viscosity fluids. See list over page for the transmission recommendations.

### Features & Benefits

#### RM Auto Premium MV Low Viscosity:

- is formulated in **full synthetic base stocks** to meet or exceed the requirements of the latest vehicles and specifications. It is designed for Australian, Asian, European and North American vehicles.
- gives **Balanced performance** in North American, European and Asian passenger car transmissions.
- Is formulated from leading additive technology
- Is a high viscosity index fluid with **multigrade viscosity characteristics** for year round protection
- provides exceptional thermal stability and oxidation resistance for long service life

The benefits of **RM Auto Premium MV Low Viscosity** are:

- Superior anti-wear performance , Enhanced oxidation resistance, Improved sludge and varnish control & Shear stability which gives **longer fluid and hardware life.**
- Expanded anti-shudder properties, Improved torque capacity, Balanced frictional stability & Improved Low Temperature properties giving **better shift feel and drivability.**
- Fortified anti-corrosion properties, Enhanced anti-corrosion properties & Enhanced foam inhibition which provide **fluid stability and hardware compatibility.**

### Specifications

Properties	Method	Result
Specific Gravity @ 20°C	ASTM D1298	0.844
Kinematic Viscosity @ 40°C	ASTM D445	30.1
Kinematic Viscosity @ 100°C	ASTM D445	6.1
Viscosity Index	ASTM D2270	156
Brookfield Viscosity @-40°C cP	ASTM D789	10,600

# RM Auto Premium MV

## Low Viscosity

Previously known as Auto Type MV Low Vis

### Performance Levels

Application	Region	Specification Name	Suitable For
Passenger Vehicles	<u>North American OEM</u>	Dexron VI	Yes
		Ford WSS-M2C949-A Ultra Low Vis	Yes
		North American Contacts	Yes
	<u>Asian OEM</u>	Aisin Warner AW-1	Yes
		DSIH 6p805 (Geely, Ssangyong, Mahindra 6 sp)	Yes
		Honda DW-1	Yes
		Hyundai/Kia SP-IV, SPH-IV, SP-IV RR	Yes
		Hyundai NWS-9638	Yes
		JASO 1-A-LV	Approved
		JWS 3324	Yes
		Mazda ATF-FZ	No
		Mitsubishi ATF-J3/ Diaqueen J3/ ATF-PA	Yes
		Mitsubishi SP-IV	Yes
		Nissan Matic D, Matic W	Yes
		Toyota WS (JWS 3324)	Yes
	<u>European OEM</u>	Audi G 055 005, G 055 162	Yes
		BMW 83 22 0 142 516, 83 22 2 152 426	Yes
		Mercedes-Benz 236.12, 236.14, 236.15, 236.18	Yes
		Mercedes-Benz 236.41	Yes
		Mercedes-Benz 236.16	No
		Saab 93 165 147	Yes
		Volvo 6 speed MY 2001-2013 (P/N 31256774 or 31256675)	Yes
		VW G 052 540	Yes
		VW G 055 005, G 005 162	Yes
		ZF 6 Speed (S671 090 255)	Yes
		ZF Lifeguard 8	Yes
	ZF Lifeguard 9	Yes	
	<u>Other Applications</u>	Conventional CVT	No

Application	Region	Specification Name	Suitable For
Commercial Vehicles	<u>Asian OEM</u>	Isuzu Gasoline (NPR and NPR-HD)	Yes
	<u>European OEM</u>	Volvo 97342	No

Master Item# 1214

Pack Size Availability: 20L & 200L

Last Updated: 30<sup>th</sup> November 2023

Previously Updated: 11<sup>th</sup> April 2023