



RM Classic Engine Oil

SAE 25W60

Previously known as Rasyn GT 60 SAE 25W60

Description

RM Classic Engine Oil SAE 25W60 is an API SP performance multigrade high viscosity engine oil manufactured from premium mineral oils. It has high detergency and superior load carrying capacity from a boosted specialty secondary zinc component which will maintain engine cleanliness and reduce wear under severe conditions of racing.

Applications

RM Classic 25W60 is formulated for use in petrol and diesel turbocharged or supercharged engines.

Features & Benefits

The high viscosity of **RM Classic 25W60** maintains a film of protective oil in the load bearing components of the engine. The formulation was specifically designed for engines subject to high stress such as conditions experienced when racing and provides:

- Superior wear protection of the engine during start-up and all driving conditions
- Excellent engine cleanliness which assists the engine to have long life and lower maintenance costs
- Superior control of ring belt and piston deposits to provide maximum power under all driving conditions
- Low oil consumption and excellent oxidative performance due to the premium base stock, shear stable formulation and specially selected metallic detergents
- Viscosity remains stable in high temperature conditions
- Increased oil film strength helps to provide protection against metal to metal contact
- High zinc formula for extra engine and flat tappet protection
- Compatible with methanol fuelled engines

Specifications

Properties	Method	Result
Specific Gravity @ 20°C	ASTM D792	0.886
Kinematic Viscosity @ 40°C	ASTM D445	258.8
Kinematic Viscosity @ 100°C	ASTM D445	24.1
Viscosity Index	ASTM D2270	117.5
Sulphated Ash %Wt	ASTM D874	1.175
Base No. mg KOH/gm	ASTM 2896-11	10.3
Phosphorus (ppm)	ASTM D3231	1,130
Zinc (ppm)	ASTM E1277	1,248
Calcium (ppm)	ASTM E508	2,893



RM Classic Engine Oil

SAE 25W60

Previously known as Rasyn GT 60 SAE 25W60

Performance Levels

API SP/CF

MB 229.1

Technical Data Sheet



Master Item# 1132

Pack Size Availability: 5L, 20L, 200L

Last Updated: 9 October 2024
Previously Updated: 9th May 2023

Sydney | Melbourne | Newcastle | New Zealand | Vietnam
AnglomOil Lubricants Group Pty. Ltd. | ABN 83 622 865 091

Int HQ: 2 Beaumont Road, Mt. Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566
Int: P +61 2 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | W www.anglomoil.com