



# SM Super 2ST Outboard

## TC-W3

Previously known as Super Outboard Motor Oil

### Description

SeaMaster Super Two-Stroke (2ST) Outboard Oil is a mineral two-stroke motor oil, suitable for high-performance water-cooled engine and for air-cooled engines. The oil has a viscosity of about SAE 40 but it is diluted with a solvent to facilitate mixing and dispersion in the fuel.

### Features & Benefits

The SM Super 2ST Outboard engine oil is particularly suitable for large water cooled two-stroke engines operating under severe conditions, e.g. High speed boats, water skiing. It can be pre-mixed with the fuel or used in direct oil injection systems at the ratio recommended by the engine manufacturer.

Benefits include:

- TC-W3 certified
- Maintains combustion chamber & exhaust system cleanliness
- Reduces smoke
- Protects against spark plug fouling
- Controls deposits and minimises wear
- Good solubility in fuel at all temperatures
- Protects against rusting
- Suitable for water cooled and air cooled engines
- Suitable for pre-mix in fuel or direct oil injection

### Specifications

Properties	Method	Results
Colour	Visual	Purple
Specific Gravity @ 15°C	ASTM D1298	0.8638
Viscosity @ 40°C	ASTM D445	39.83
Viscosity @ 100°C	ASTM D445	7.06
Viscosity Index	ASTM D2270	139.7
Total Base Number	ASTM D2896-11	5.2
Flash Point °C	ASTM D92	98

Master Item# 1407

Pack Size Availability: 5L, 20L, 200L, IBC=1000L

Last Updated: 6<sup>th</sup> December 2023  
Previously Updated: 15<sup>th</sup> March 2021

Sydney | Melbourne | Newcastle | New Zealand | Vietnam  
AnglomOil Lubricants Group Pty. Ltd. | ABN 83 622 865 091

Int HQ: 2 Beaumont Road, Mt. Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566  
Int: P +61 2 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | W www.anglomoil.com