

Product Description

Anglomoil Slideway Oil series are high performance, ashless slideway lubricants based on solvent refined minerals oils.

Product Features & Benefits

Anglomoil Slideway Oil's utilise the proven technology in lubricity, extreme pressure and demulsibility to provide optimum performance in use. They use:

- Strong demulsibility and water separation performance
- Proven stick slip performance which is required for repeatable machining
- Exceptional anti-staining and anti-corrosion properties
- Light colour and low odour
- Excellent anti-wear and extreme pressure performance
- Non-corrosive to both ferrous and non-ferrous alloys
- Excellent filterability
- Compatibility with commonly used cutting fluids

Additional Information

Anglomoil Slideway Oils:

- Are recommended for both vertical and horizontal slideways where high quality demulsifying slideway lubricants are required
- Can be used for both metal and plastic slideways

Typical Characteristics

Test	Test Method	ISO 68	ISO 220
Density @ 20 °C	IP 160	0.878	0.893
Viscosity @ 40°C	ASTM D445	72.5 cSt	214 cSt
Viscosity @ 100°C	ASTM D445	9.5 cSt	19.2 cSt
Viscosity Index	IP 26	109	101

Performance Levels

Anglomoil Slideway Oil meets all the requirements for:

Slideway Lubricants	Cincinnati Lamb P-47
Hydraulic & Industrial gear Oil	DIN 5124-2 HLP DIN 51517-3 CLP
Additional Performance	Bijur Filtration Testing SKC Coolant Separability Darmstadt Test Protocols

Master Item# 2610 & 2606
 Pack Size Availability: 20L, 200L, IBC=1000L

Last Updated: 12th March 2021