

Super Outboard Motor Oil

Anglomoil Super Outboard Motor Oil is a current state of the art two stroke motor oil, suitable for high performance water cooled engines and for air cooled engines.

It is formulated from highly refined base oils blended with a synthetic component and ashless performance additives to meet the exacting requirements of the National Marine Manufacturers Association TC-W3 specification.

The oil has a viscosity of about SAE40 but it is diluted with a solvent to facilitate mixing and dispersion in the fuel.

Anglomoil Super Outboard Motor Oil is particularly suitable for large water cooled two stroke engines operating under severe conditions, eg high speed boats, water skiing. It can be pre-mixed with the fuel, or used in direct oil injection systems at the ratio recommended by the engine manufacturer.

Smaller, high performance air cooled motors can also benefit from the properties of Super Outboard Motor Oil, and it is recommended for chain saw motors and even racing go-cart motors!

- TC-W3 certified
- Maintains combustion chamber & exhaust system cleanliness
- Reduces smoke
- Protects against spark plug fouling
- Controls deposits and minimises wear
- Good solubility in fuel at all temperatures
- Protects against rusting
- Suitable for water cooled and air cooled engines
- Suitable for pre-mix in fuel or direct oil injection

Typical Characteristics

Density @ 15 °C, kg/L	0.817
Viscosity @ 40°C	40.9
Viscosity @ 100°C	7.09
Viscosity Index	135.2
Total Base Number	5.2
Flash Point °C	98
Colour	Purple

Master Item# 1407

Pack Size Availability: 5L, 20L, 200L, IBC=1000L

Last Updated: 15th March 2021