



# RASYN GT R 50

## 10W50

### Description

**RASYN GT R50** is an API SP/CF, ACEA A3/B3/B4 performance multigrade high viscosity engine oil manufactured from synthetic oils. It has high detergency and superior load carrying capacity from a boosted specialty secondary zinc component which will maintain engine cleanliness and reduce wear under severe conditions of racing.

### Features & Benefits

The high viscosity of **RASYN GT R50** maintains a film of protective oil in the loadbearing components of the engine. The formulation was specifically designed for engines subject to high stress such as conditions experienced when racing and provides:

- Superior wear protection for the engine during start-up and all driving conditions
- Excellent engine cleanliness which assists the engine to have long life and lower maintenance costs
- Superior control of ring belt and piston deposits to provide maximum power under all driving conditions
- Low oil consumption and excellent oxidative performance due to the synthetic base stock, shear stable formulation and specially selected metallic detergents
- Viscosity remains stable in high temperature conditions
- Increased oil film strength helps provide protection against metal to metal contact
- High zinc formula for extra engine and flat tappet protection

RASYN GT R50 10W50 is formulated for use in petrol and diesel turbocharged or supercharged engines.

### Specifications

Properties	Result
Specific Gravity @ 20°C	0.8499
Kinematic Viscosity @ 40°C	114.1
Kinematic Viscosity @ 100°C	17.94
Viscosity Index	174.8
Sulphated Ash %Wt	1.26
Base No. mg KOH/gm	10.3
Phosphorus (ppm)	1,246
Zinc (ppm)	1,364
Calcium (ppm)	1,928

### Performance Levels

API SP / CF	VW 502.00
ACEA A3 / B3 / B4	MB 229.1
Fiat 9.55535-H3	BMW M (meets requirements)

Master Item# 1020

Pack Size Availability: 5L, 20L, 200L

Last Updated: 12<sup>th</sup> August 2024

Sydney | Melbourne | Newcastle | New Zealand | Vietnam  
AnglomOil Lubricants Group Pty. Ltd. | ABN 83 622 865 091

Int HQ: 2 Beaumont Road, Mt. Kuring-gai NSW 2080 Australia | Australia: P 1300 264 566  
Int: P +61 2 9457 8566 | F +61 2 9457 8057 | E info@anglomoil.com | W www.anglomoil.com