



Product Description

Anglomoil SFG Gear Oils are made from synthetic hydrocarbons (PAO) and special additive packages and are **NSF H-1** listed for use where incidental food contact can occur.

SFG Gear Oils are recommended for gear sets, bearings, circulating oil systems and chain applications in food processing machinery. The heavier viscosity grade provides excellent service in worm gear units.

Synthetic Versatility

Anglomoil SFG Gear Oil is formulated from synthetic Poly Alpha Olefin, renowned for its excellent thermal stability and high viscosity index. This high performance is further enhanced by Anglomoil's unique additive system.

The selected formulation is especially effective for use in a wide range of industrial gearboxes.

Synthetic Durability

Anglomoil SFG Gear oils will provide a far longer service life than most mineral based lubricants.

Longer life with fewer oil changes,

Extended equipment life

Reduced energy costs

Excellent high and low temperature operations

Increased oxidative stability

Compatibility

Anglomoil PAO lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an Anglomoil synthetic hydrocarbon-based lubricant.

WO Food Grade Gear Oil Indicative Properties

Grade	NSF Registration	Base Fluid	ISO Grade	Viscosity cSt		Viscosity Index	Specific Gravity @ 15.6°C	Flash Point °C	Pour Point °C
				40 C	100 C				
				SFG Gear Oil 68	145936				
SFG Gear Oil 100	145937	PAO	100	100	13.5	135	TBA	TBA	-35
SFG Gear Oil 150	145938	PAO	150	150	18.3	137	TBA	TBA	-35
SFG Gear Oil 220	132398	PAO	220	215	21.9	137	0.86	224	-35
SFG Gear Oil 320	132397	PAO	320	324	32	138	0.865	230	-35
SFG Gear Oil 460	139919	PAO	460	466	42	141	0.867	235	-35
SFG Gear Oil 680	139920	PAO	680	680	56	142	0.87	240	-35

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: