



### Product Description

Anglomoil WO Hook Oil is made from Paraffinic white Oils and special additive packages and are **NFS H-1** listed for use where incidental food contact can occur.

WO Hook Oils are recommended for Hook applications in food processing machinery.

### Product Features and Benefits

Anglomoil WO Hook Oil is formulated from Paraffinic white Oils and have good thermal stability and lubricity. This high performance is further enhanced by Anglomoil's unique additive system.

Anglomoil WO Hook oils will provide good service life.

- Excellent corrosion protection to the Hook providing longer service life
- Good high and low temperature operations
- Good oxidative stability

### Compatibility

Anglomoil white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an Anglomoil white oil hydrocarbon-based lubricant.

PRODUCT DATA SHEET

White Mineral Oil		ISO 15
<b>Approvals</b>	<b>NSF Listed #</b>	<b>145951</b>
Appearance		Water white
Colour	Saybolt	+30 min
Brookfield Viscosity 40°C cPs	TM2201	Report
Kinematic Viscosity, at 40°C cSt	ASTM D445	13.8 - 16.5
Pour Point	ASTM D97	-9.4 °C typ
Flashpoint	ASTM D92	185 °C typ
Polycyclic aromatic hydrocarbons	TM 1606	Conform BP
Readily Carbonisable Substances	BP 2002	Conform BP
Solid Parafins	BP 2002	Conform BP
Specific Gravity		0.853 typ

#### Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com